

005/6/8

VERY HIGH ACCURACY DECADE BOXES WITH VERSATILE WIDE OHM RANGE

A versatile range of resistance decade boxes available in 5, 6 & 8 decades. High Accuracy and wide range 0.001 ohm to 11 Mega ohm are combined in a compact lightweight metal case. The switches have gold plated contacts to ensure a low contact resistance and negligible thermal E.M.F. Some models employ the Waidner Wolf technique to eliminate the errors switch contact resistance and are particularly suited to Pt100 simulation with resolution as low as 0.001 ohm (» 0.0025°C).

KEY FEATURE	005/6/8
High accuracy 0.01% and high performance	■
Suitable for Pt100 and transducer simulation	■
5, 6 and 8 Decades	■
Long term stability ± 20ppm/year	■
Low temperature co-efficient ± 3ppm/°C to + 85 °C	■
Gold-plated switch contacts and solid copper input terminals	■
Negligible thermal E.M.F.'s	■
Light weight / small size	■
With certificate of conformity	■
In-house test figures optional	■



005/6/8 SPECIFICATIONS

010-A	008-C	008-B	008-A	006-C	006-B	006-A	005-B	Decade	Accuracy	Current Max
			■			■		10 x 0.001Ω	± 2%	1.4A
■		■	■		■	■	■	10 x 0.01Ω	± 1%	1.4A
■	■	■	■	■	■	■	■	10 x 0.1Ω	± 0.5%	1.4A
■	■	■	■	■	■	■	■	10 x 1Ω	± 0.2%	300mA
■	■	■	■	■	■	■	■	10 x 10Ω	± 0.01%	100mA
■	■	■	■	■	■	■	■	10 x 100Ω	± 0.01%	30mA
■	■	■	■	■	■			10 x 1kΩ	± 0.01%	18mA
■	■	■	■	■				10 x 10kΩ	± 0.01%	5mA
■	■	■						10 x 100kΩ	± 0.01%	1.8mA
■	■							10 x 1MΩ	± 0.01%	0.5mA
■								10 x 10MΩ	± 0.25%	0.18mA

Model	No. Decades	Total Resistance	Resolution	Suitable for Pt100 Simulation	Resolution °C when Simulating Pt100	Residual Resistance Ω
005-B	5	1,112.10Ω	0.01	■	0.025	1Ω
006-A	6	1,112.11Ω	0.001	■	0.0025	1Ω
006-B	6	11,112.10Ω	0.01	■	0.025	1Ω
006-C	6	111,111Ω	0.1	—	—	70mΩ
008-A	8	111,112.11Ω	0.001	■	0.0025	1Ω
008-B	8	1,111,112.1Ω	0.01	■	0.025	1Ω
008-C	8	11,111,111Ω	0.1	—	—	80mΩ
010-A	10	111,111,111,1Ω	0.1	■	0.025	1Ω

Calibration

Calibration certificates including UKAS traceable are available on request

Switches

Contact material gold plated brass
 Contact resistance = 5 mohm
 Insulation Resistance (all paths = 10Gohm)
 Proof voltage 1kV

Resistors

Temperature Co-efficient:
 ±3ppm / +20°C to + 85°C ±5ppm maximum over -55°C to +125°C 0.1, 0.01, & 0.001 dials 10ppm/°C

Full Load Stability:
 ±35ppm/10,000 hours
 ±50ppm/26,000 hours

No Load Stability:
 ±25ppm/10,000 hours
 ±35ppm/26,000 hours

Over full temperature range:
 -50°C to +125°C

Power Rating:
 0.33 watt (+85°C) 0.25 watt (+110°C)

Maximum Continuous Working Voltage:

Up to 250 V dc

Noise:

Essentially non-measurable <1.5µV

Thermal E.M.F.:

<0.4µV

Encapsulation:

Moulded epoxy

Windings:

Exclusive 'air cushioned' technique provides virtually stressless elements for improved performance. Non inductively wound. Direction of winding reversed at half turns point

Weight

005 - 0.5kg
 006 - 0.6kg
 008 - 0.8kg
 0010 - 1kg

Size

350mm x 100mm x 80mm (W H D) approx